

MICRO BIRD® MB-II GM - SCHOOL BUS



Economical transportation for up to 20 passengers



Integrated child seats and 3-point lap and shoulder seat belts* are available for enhanced safety and versatility.

**FMVSS 208 requires 3-pts seat belts in all school buses with a GVWR less than 10,000 lbs.*



Maximum visibility of loading zone is provided by fully-glassed entrance door and unobstructed "More-View" window.

Standard 24" electric double-opening door.



LED clearance lights, direction lights, stop lights and back-up lights are standard equipment offering enhanced safety, while reducing operating and maintenance costs.



Also Available:

Special needs Micro Bird with single-leaf wheelchair door which meets FMVSS/CMVSS 206 standards.

COUNT ON BLUE BIRD
LEARN MORE AT WWW.BLUE-BIRD.COM



MICRO BIRD® MB-II GM - SPECIFICATIONS



BODY DIMENSIONS	MODEL	400	500	700	800
	Max. pass. capacity (US/Can)	20	18/20	20	13/14
	Number of rows	4	5	4	5
	Exterior length overall	234"	254"	234"	254"
	Exterior width overall	86"	86"	86"	86"
	Exterior height overall	101"	101"	109"	109"
	Interior floor length	131"	156"	131"	156"
	Interior width at hip	82"	82"	82"	82"
	Interior height at center line	66"	66"	74"	74"
	Entrance door	24" x 70"	24" x 70"	24" x 77"	24" x 77"
Side windows	23" x 22"	23" x 22"	31" x 22"	31" x 22"	
Rear bumper	3/16" x 8" with 12" wrap around				
GMC / CHEVY CHASSIS	MODEL	400	500	700	800
	Wheelbase	139"			
	Engine	4.8 L gas / 6.0 L gas / 6.6 L diesel			
	Transmission	6-speed automatic heavy duty overdrive			
	GVWR	9,900 lbs / 10,100 lbs			
	Fuel tank	33 gallons			
	Brakes	4-wheel anti-lock, 4-wheel disc			
	Tires	LT245/75R16E all-season, blackwall			
	Alternator	145 amp			
Battery	600 CCA (gas) / 2 x 770 CCA (diesel)				

STANDARD BODY EQUIPMENT	8 ways (4 amber and 4 red)	Mirrors rearview
	8 ways black around vinyl tape	Padding all doors
	Bumper aluminum	Paint exterior yellow
	Emergency triangular warning device*	Paint interior white
	Entrance door electric	Paint rub rail black
	Entrance door grab handle left	Rear door 2 windows
	Floor plywood 1/2" (4 ply)	Rear door 3 point slide bar latch
	Flooring grey rib in aisle	Rear door buzzer
	Flooring grey smooth under seat	Rear door retainer*
	Flooring steps grey with white nosing	Reflective tape rear emergency exit*
	FMVSS seat belt anchorage	Roof bow one piece, hat section type
	Heater 20,500 BTU	Rub rail floor level
	Interior below window embossed aluminum	Rub rail seat level with wrap around
	Interior mirror 6" x 16"	Shut-off valve under body
	Joint strength	Speakers (2)
Lights clearance LED	Stepwell light LED	
Lights dome (4)	Stop arm	
Lights marker LED	Undercoating	
Lights back-up LED	Windows back (2) tinted 62%	
Lights stop and tail LED	Windows rear door tinted 62%	
Lights turn LED	Windows side tinted 62%	
Mirrors crossview	*Standard in the US, optional in Canada	

OPTIONS	Air conditioning	Lift door with tinted windows
	Audio / P.A. systems	Lift wheelchair
	Back-up sensors	Lift wheelchair tie-down
	Barriers	Light monitoring system
	Bumper steel	Luggage containment systems
	Driver side auxiliary step	Paint roof white
	Electronic sleeping child monitoring system	Reflective exterior signs
	Emergency equipment	Remote / heated mirrors
	Entrance door grab handle right	Rub rail skirt level
	Floor plywood 5/8" (5 ply) marine grade	Rub rail window level
	Floor steel	Seats
	Heater 42,000 BTU	Vandal lock system
	Integrated toddler seats	Wheelchair and occupant restraint system
	Lap and shoulder belt seating	Wheelchair lift with interlock device
	Lift door	

More options available...

Specifications shown in this brochure were in effect at time of printing. In keeping with its policy of continual improvement, Micro Bird, Inc. reserves the right to change specifications without notice and without incurring obligations.



Galvanized Steel Structure and Side Impact Barriers

- Steel body frame ensures that all exterior elements, including dust, moisture and noise, remain outside the passenger compartment.
- Superior side impact protection is offered by the use of heavy-gauge steel side impact barriers that incorporate the seat rail into the design for extra strength.



Double Action Energy Absorbing Body Mounting Blocks

- Absorb road vibration
- Reduce noise transfer to the cabin interior
- Offer extended body durability
- Smoother passenger ride
- Prevent frame collapse
- Eliminate the need for periodic tightening of body bolts



Superior Insulation

- 1.5" fiberglass throughout
- Insulated roof bows
- Reduction in noise transfer into passenger compartment
- Prevents condensation.



Patented Extra Wide Oval Body

- Aerodynamic styling
- Wider seating for increased comfort
- Wider aisle for increased safety
- Better compartmentalization

Floor Plans

A wide range of configurations to better accommodate your needs.

