

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name	HEAVY DUTY SAE 75W90 SYNTHETIC GEAR OIL
Product code	3196
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, amber

NOTICE: WHILE THIS MATERIAL HAS A LOW LEVEL OF TOXICITY, GOOD INDUSTRIAL HYGIENE PRACTICES ARE ENCOURAGED TO MINIMIZE EXPOSURE.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

Unlikely to cause skin irritation or injury.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
PROPRIETARY SYNTHETIC GEAR LUBRICANT		>=90-<=100%
OLEFINSULFIDE	68937-96-2	>=5-<10%

4. FIRST AID MEASURES

Eyes

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus

Precautions for fire-fighting

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear resistant gloves such as:

Latex gloves

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	no data available
Colour	amber
Odour	pungent
Boiling point/boiling range	no data available
Melting point/range	no data available
Sublimation point	no data available
pH	no data available
Flash point	419 °F / 215 °C Closed Cup
Ignition temperature	no data available
Evaporation rate	no data available
Lower explosion limit/Upper explosion limit	no data available
Particle size	no data available
Vapour pressure	no data available
Relative vapour density	no data available
Density	0.8780 g/cm ³ @ 60.01 °F / 15.56 °C
Bulk density	No data
Water solubility	insoluble
Solubility(ies)	no data available
Partition coefficient: n-octanol/water	no data available
log Pow	no data available
Autoignition temperature	no data available
Viscosity, dynamic	no data available
Viscosity, kinematic	no data available
Solids in Solution	no data available
Decomposition temperature	no data available
Burning number	no data available
Dust explosion constant	no data available
Minimum ignition energy	no data available

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, sulfur compounds

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

PROPRIETARY SYNTHETIC GEAR LUBRICANT : LD 50 Rat: > 2,000 mg/kg

OLEFINSULFIDE : LD 50 Rat: 6,500 mg/kg

Acute inhalation toxicity

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Acute dermal toxicity

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

PROPRIETARY SYNTHETIC GEAR LUBRICANT : Not readily biodegradable.

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

OLEFINSULFIDE : no data available

Bioaccumulation

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Ecotoxicity effects

Toxicity to fish

PROPRIETARY SYNTHETIC GEAR LUBRICANT : LC 50 Fish: 10.00 - < 100.00 mg/l

OLEFINSULFIDE : no data available

Toxicity to daphnia and other aquatic invertebrates.

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Toxicity to algae

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Toxicity to bacteria

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Biochemical Oxygen Demand (BOD)

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Chemical Oxygen Demand (COD)

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

Additional ecological information

PROPRIETARY SYNTHETIC GEAR LUBRICANT : no data available

OLEFINSULFIDE : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.	2-NAPHTHALENAMINE
---	-------------------

SARA Hazard Classification

No SARA Hazards

New Jersey RTK Label Information

PROPRIETARY SYNTHETIC GEAR LUBRICANT
MIXTURE OF OLEFIN SULFIDE, H2OP4 ESTER, AMINE SALTS,
ALKYLSULFIDE, ALKENYLAMIDE AND OTHER INGREDIENTS
OLEFINSULFIDE

68937-96-2

Pennsylvania RTK Label Information

PROPRIETARY SYNTHETIC GEAR LUBRICANT
MIXTURE OF OLEFIN SULFIDE, H2OP4 ESTER, AMINE SALTS,
ALKYLSULFIDE, ALKENYLAMIDE AND OTHER INGREDIENTS

HEAVY DUTY SAE 75W90 SYNTHETIC
GEAR OIL
3196

OLEFINSULFIDE

68937-96-2

Notification status

US. Toxic Substances Control Act	y (positive listing)
Japan. Kashin-Hou Law List	n (Negative listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	n (Negative listing)
China. Inventory of Existing Chemical Substances	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	n (Negative listing)
Canada. Canadian Environmental Protection Act (CEPA). Non-Domestic Substances List (NDSL) (Can. Gaz. Part II, Vol. 133)	y (positive listing)

	HMIS	NFPA
Health	1	0
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).