



if it matters, we're on it.®

SAFETY DATA SHEET

Revision date 28-May-2015

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 400.0002029.076

Product Name T-29 SCHOOL BUS YELLOW 6UC

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Aerosol, Paint

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

Section 2: HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 2
Gases under pressure	Liquefied gas

Label elements

Product Code 400.0002029.076

Page 1 / 10

AGHS - USA OSHA SDS



Signal word

WARNING

HAZARD STATEMENTS

Flammable aerosol
Contains gas under pressure; may explode if heated
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C).

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

OTHER HAZARDS

Causes mild skin irritation.

UNKNOWN ACUTE TOXICITY

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Acetone	67-64-1	25 - 50
2-Pentanone, 4-methyl-	108-10-1	10 - 25
n-Butyl acetate	123-86-4	5 - 10
Xylenes	1330-20-7	1 - 3
Titanium dioxide	13463-67-7	1 - 3

Product Code 400.0002029.076

Page 2 / 10

AGHS - USA OSHA SDS

Zirconium ethyl hexoate	22464-99-9	0.3 - 1
Ethylbenzene	100-41-4	0.3 - 1
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	0.1 - 0.3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF EXPOSED OR CONCERNED: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in appropriate containers for disposal. Pick up and transfer to properly labeled containers.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Considerations

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect from sunlight. Store in a well-ventilated place.

Incompatible materials

Strong bases. Strong oxidizing agents. Strong reducing agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
2-Pentanone, 4-methyl- 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³

Zirconium ethyl hexoate 22464-99-9	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	No information available
Odor	Solvent
Color	yellow
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	-35 °C / -31 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	6.42
specific gravity	.77
Solubility(ies)	Not Determined
Partition coefficient	No information available
Autoignition temperature	No information available

Product Code 400.0002029.076

Page 5 / 10

AGHS - USA OSHA SDS

Decomposition temperature No information available
 Kinematic viscosity No information available
 Dynamic viscosity No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity No information available.
Chemical stability Stable under normal conditions.
Possibility of Hazardous Reactions None under normal processing.
Hazardous polymerization None under normal processing.
Conditions to avoid Heat, flames and sparks.
Incompatible materials Strong bases. Strong oxidizing agents. Strong reducing agents.
Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
 Causes serious eye irritation
Skin Contact
 May cause an allergic skin reaction
Ingestion
 Not applicable
Inhalation
 May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	-	-	= 50100 mg/m ³ (Rat) 8 h
2-Pentanone, 4-methyl- 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
n-Butyl acetate 123-86-4	= 14.13 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Xylenes 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Zirconium ethyl hexoate 22464-99-9	-	-	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7	-	-	-

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 73752 Mg/kg
 ATEmix (inhalation-dust/mist) 12.2 mg/l
 ATEmix (inhalation-vapor) 89 mg/l

UNKNOWN ACUTE TOXICITY .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Product Code 400.0002029.076

Page 6 / 10

AGHS - USA OSHA SDS

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Pentanone, 4-methyl- 108-10-1	A3	Group 2B		X
Titanium dioxide 13463-67-7		Group 2B		X
Ethylbenzene 100-41-4	A3	Group 2B		X
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation	Not applicable
Serious eye damage/eye irritation	Causes serious eye irritation
Skin sensitization	May cause an allergic skin reaction
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Suspected of causing cancer
Reproductive Toxicity	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure)	Not applicable
Aspiration hazard	Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

14.1 UN/ID no	DOT ORM-D	IMDG UN1950	IATA UN1950
14.2 Proper shipping name	CONSUMER COMMODITY	Aerosols	Aerosols
14.3 Hazard Class		2.1	2.1
14.4 Packing Group			
14.5 Environmental hazard	Not applicable		
14.6 Special Provisions			
	Emergency Response Guide Number 126	EmS-No F-D, S-U	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available		

Section 15 REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
2-Pentanone, 4-methyl- 108-10-1 10 - 25	1	Present
Xylenes 1330-20-7 1 - 3	1	Present
Ethylbenzene 100-41-4 0.3 - 1	0.1	Present
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7 0.1 - 0.3	1	Present

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			X
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
2-Pentanone, 4-methyl- 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

Product Code 400.0002029.076

US State Regulations

Rule 66 status of product
Not photochemically reactive.

California Proposition 65
WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Acetone 67-64-1
Propane 74-98-6
Proprietary Non-Hazardous Ingredient - Proprietary CAS
2-Pentanone, 4-methyl- 108-10-1
Butane 106-97-8
n-Butyl acetate 123-86-4
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Xylenes 1330-20-7
Titanium dioxide 13463-67-7
Zirconium ethyl hexoate 22464-99-9
Ethylbenzene 100-41-4
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal
Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system

Section 16 OTHER INFORMATION

HMIS

Health hazards 2*
* = Chronic Health Hazard
Flammability 4
Physical hazards 0
Personal Protection X

Supplier Address

Valspar Consumer Headquarters 8725 W. Higgins Rd. Suite 1000 Chicago, IL 60631 773-628-5500	The Valspar Corporation 4999 36th St. Grand Rapids, MI 49512 800-253-3957	Valspar Plasti-Kote 1636 Shawsone Dr. Mississauga, Ontario L4W 1N7 905-671-8333
------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------

Prepared By

Product Stewardship

Revision date

28-May-2015

Revision Note

No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

End of Safety Data Sheet